



Smart Access Controlling System based on NXP i.MX 6UltraLite CPU



Specification

CPU	NXP i.MX 6UltraLite ARM Cortex®-A7 CPU, i.MX 6ULL (optional)
RAM	256MB DDR3 RAM (128MB/512MB optional)
Storage	4GB eMMC (8GB/16GB/32GB optional)
OS	Linux 4.1.15 kernel
Functions	1 x RJ45 10/100M
	4 x Wiegand signal, supporting 26/34/37bit
	4 x RS485 half duplex interface
	1 x CAN bus
	LED indicator IO output
	4 x BEEP doorbell IO output
	4 x HOLD door lock IO output
	4 x 12V DV output, each up to 400mA@12V
Power	4 x electric lock control output
	12V 2A DC input
Size	15 x 15 x 6cm

ABOUT POLYHEX

As a board level and system level designer and manufacturer, Polyhex, with 9 years' experience, always delivers best-in-class embedded computing solutions based on both ARM and X86 architecture, including hardware customization and software debugging etc. Partnered with silicon vendors like Intel, NXP, ST, Rockchip, Allwinners and so on, we have earned trust from clients worldwide in over 30 countries. Polyhex is also certified with ISO9001 and ISO13485 for the self-owned manufacture facility.

