


Embedded Motherboard Based on Rockchip RK3399 CPU



















Specification:

| СРИ | RK3399 |
|--------------------|---|
| | Dual-core Cortex-A72 up to 1.8GHz + Quad-core Cortex- |
| | A53 up to 1.4GHz |
| GPU | Mali-T860MP4 GPU, Support OpenGL ES1.1/2.0/3.0/3.1, |
| | OpenVG1.1, OpenCL, DX11 |
| DDR | 2GB Double-Channel 64bit LPDDR4, Support 4GB |
| Flash | 16GB eMMC5.1, Support 8GB/32GB/64GB/128GB |
| WIFI&BT | WIFI2.4G/5G, BT4.0 |
| USB OTG | 1 x USB OTG, Type-C Connector |
| Earphone | 1 x φ3.5mm Earphone Out, With Mic in |
| TF | 1 x TF Card Slot |
| SIM | 1 x SIM Card Slot |
| HDMI | 1 x HDMI OUT |
| USB3.0 | 4 x USB3.0, USB A-Type Connector |
| RJ45 | 1 x 10/100/1000M LAN Port |
| Mini PCle | 1 x Mini PCle Slot For 4G Module |
| CSI | 1 x 4 Lane CSI MIPI In For Camera |
| DSI | 1 x 4 Lane DSI MIPI Out For LCD |
| TP | 1 x Touch Panel(I2C interface) |
| LVDS | 1 x Double Channel 8bit LVDS OUT |
| eDP | 1 x 4 Lane eDP OUT |
| Extended interface | 1 x TTL UART For DEBUG |
| | 4 x RS232(Default) Or TTL UART(Select) |
| | 2 x RS485(Default) Or RS232(Select) Or TTL UART(Select) |
| | 3 x USB2.0 |
| | 2 x Speaker Out |
| | 1 x Audio in |
| | 12 x GPIO |
| | 4 x I2S In |
| | 2 x ADC In |
| | 1 x IR In |
| | 1 x PWM |
| | 1 x RTC |
| | 2 x KEY, Power Key and Recovery Key |
| OS | Android7.1/ubuntu16.04, android 9.0/debian9 |
| Power In | DC 12V/2A |
| Size | 146 x 102 x 16mm |



ABOUT POLYHEX

As a board level and system level designer and manufacturer, Polyhex, with 9 years' experience, always delivers best-in-class embedded computing solutions based on both ARM and X86 architecture, including hardware customization and software debugging etc. Partnered with silicon venders like Intel, NXP, ST, Rockchip, Allwinners and so on, we have earned trust from clients worldwide in over 30 countries. Polyhex is also certified with ISO9001 and ISO13485 for the self-owned manufacture facility.

